



FERMOD®

Technical Description

FERMOFLEX PVC STRIP CURTAINS

FERMOFLEX PVC strip curtains are suitable for a wide range of applications including cold rooms, hygiene areas, and noise or light sensitive environments. The profiles are very resistant to corrosion and easy to clean. The strips can be fixed or replaced singularly.

Complying with the HACCP program, the FERMOFLEX strip curtain allows to:

- Minimise the temperature variations
- Increase the lifetime of the refrigeration components
- Save energy
- Helps prevent ice formation in negative temperatures and therefore improve Health & Safety

4 Standard models:

2620 FIXED STRIP CURTAIN - COMPOSITE

Ease and rapidity of installation
Supplied with standard length mounting header (8 lengths)
For strips 190 x 2 mm with choice of 40 or 80% overlap of strips
For strips 300 x 3 mm with 50% overlap of strips
Profile equipped with pre-mounted hooks ready to use, manufactured in composite, identical for 40%, 50% or 80% overlap of strips

2600 FIXED STRIP CURTAIN – ANODIZED ALUMINIUM

Supplied with standard length mounting header (22 lengths)
For strips 190 x 2 mm with choice of 40 or 80% overlap of strips
For strips 300 x 3 mm with choice of 50 or 75% overlap of strips
Profile and elements of profile manufactured in Aluminium

2700 SWINGING STRIP CURTAIN – ANODIZED ALUMINIUM

Swinging in both directions, to ease access and to increase the durability of the strips
Wall and/or ceiling mounting
Supplied with standard length mounting header (8 lengths)
Strips 190 x 2 mm or 300 x 3 mm
Overlap according to strip width

DO IT YOUR SELF STRIP CURTAIN

Header supplied in standard lengths to cut + accessories
Profile and hooks in composite or profile and elements of profile in Aluminium
Strips 190 x 2 mm or 300 x 3 mm to choose

STRIP FEATURES

Standard quality for positive temperature – 10°C to + 50°C
Low temperature quality for negative temperature – 40°C to + 10°C
Orange end strips only available for standard quality
Doorstrips made of compatible materials for occasional food contact and classified Euroclass B1 (M1) in the fire resistance scale

All strips are available in bespoke lengths and 50 m rolls.

On request:

Thickness 4 mm for strips 190 mm & 300 mm

Options :

- Ceiling fixing for ref. 2620 (1 bracket every 450 mm) and for ref. 2600 (1 bracket every 750 mm maximum)
- Sliding curtains
- Kit FERMOFLEX 2620 strip curtain: packaging in kit for easy storage