



## Technical Description

# FERMOSTOCK 6611/6811/6811B

*Shelving structure (rails + uprights) Anodized Aluminium (Class 15) equipped with removable shelf inserts withstanding temperatures down to - 40° C*

### NF Food Hygiene Label assigned by AFNOR Certification

11, Avenue Francis de Pressensé – 93571 Saint Denis La Plaine Cedex - France  
*This label guarantees to conformity to the NF031 standard. Statutory requirement: cleanability.*

[www.marque-nf.com](http://www.marque-nf.com)

### NSF Label « Food Equipment »



### Three versions

- Ref. 6611 : with Polymer shelf inserts
- Ref. 6811 : with Anodized Aluminium shelf inserts
- Ref. 6811/B : with shelf inserts in Anodized Aluminium for small packages

### Dimensions

- 4 heights : 1685 mm – 1800 mm – 2100 mm – 2400 mm (contact us for other dimensions)
- 3 depths : 360 mm (Gastro 1/1 and 2/3) – 460 mm – 560 mm (Gastro 1/1 and 2/1)
- 10 lengths : 660, 780, 900, 960, 1080, 1200, 1320, 1500, 1620, 1740 mm

### Specifications

- High rigidity due to the conception of assembly (patented) through conic metal clips manufactured in anodized aluminium ensuring extremely stable units,
- Return angle on the full depth with complete unobstructed access,
- Quick and easy assembly, without tools,
- Possibility of adjusting levels without tools of 150 mm increments to desired height
- Fine adjustment with composite inserts
- Operating temperature (-40°C/+60°C)
- Easy cleaning through the use of removable shelf inserts (machine washable up to +100°C)
- Uprights delivered neutral without clip, but these are delivered with the shelf inserts
- Fully accessible from both sides as no crossed bracing is required
- Possible mounting configurations straight , "L", "U", "T" and "+"
- Anodized Aluminium shelf inserts are reversible (flat tube or half-round)
- Possibility of mixing the different qualities of shelf inserts: 6611, 6811, 6811/B, 6622
- Maximum weight/level : 175 kg for ref. 6611, 250 Kg for ref. 6811 evenly distributed load
- Maximum weight: 900 Kg between two uprights, and 600 kg between two uprights with angle configuration.

### Options

- Label holder for shelving systems Fermostock 6611 - 6811 - 6811/B - 6622
- Wall fixation and ground fixation for Fermostock 5711 - 6611 – 6811 - 6811/B - 6622
- Collecting containers adaptable to all lengths of shelf levels (depth: 460 mm) for Fermostock 6611 - 6811 - 6811/B – 6622

### Variants

- Mobile shelving height 1800 and 1907 mm
- Low fixed shelving height 300 mm
- Low mobile shelving height 440 mm