



FERMOD®

Technical Description

FERMOSTOCK

MOBILE

*Shelving mobile structure (uprights with composite castors + bars)
Duralinox Anodized Aluminium (Class 15) equipped with removable shelf inserts
with standing a temperature of - 40 ° C*

NF Food Hygiene Label assigned by AFNOR Certification

11, Avenue Francis de Pressensé – 93571 Saint Denis La Plaine Cedex – France
This label guarantees to conformity to the NF031 standard. Statutory requirement: cleanability.

NSF Label « Food Equipment »



Three versions

- Ref. 6611 : with Polymer shelf inserts
- Ref. 6811 : with Anodized Aluminium shelf inserts
- Ref. 6811/B : with shelf inserts in Anodized Aluminium for small packages

Dimensions

- Height including castors: 1792 mm (contact us for other dimensions)
- 3 depths : 360 mm (Gastro 1/1 and 2/3) – 460 mm – 560 mm (Gastro 1/1 and 2/1)
- 10 lengths : 660, 780, 900, 960, 1080, 1200, 1320, 1500, 1620, 1740 mm

Specifications

- High rigidity due to the conception of assembly (patented) through conic metal clips manufactured in anodized aluminium ensuring extremely stable units,
- Quick and easy assembly, without tools,
- Possibility of adjusting levels without tools of 150 mm increments to desired height
- Easy cleaning through the use of removable shelf inserts (machine washable up to +100°C)
- Uprights delivered neutral without clip, but these are delivered with the shelf inserts
- Operating temperature: -40°C / +60°C
- Equipped with 4 composite castors including 2 with brakes (Ø 125 mm),
- Fully accessible from both sides as no crossed bracing is required
- Anodized Aluminium shelf inserts are reversible (flat tube or half-round)
- Possibility of mixing the different qualities of shelf inserts: 6611, 6811, 6811/B, 6622
- Maximum weight/level : 120 kg for ref. 6611, 200 Kg for ref. 6811 evenly distributed load
- Maximum weight between two uprights: 240 Kg

Options

- Label holder for shelving systems Fermostock 6611 - 6811 - 6811/B – 6622
- Collecting containers adaptable to all lengths of shelf levels (depth: 460 mm) for Fermostock 6611 - 6811 - 6811/B – 6622

Variants

- Fixed shelving height : 1685 mm, 1800 mm, 2100 mm and 2400 mm
- Low fixed shelving height 300 mm and low mobile shelving height 440 mm