




Fixed and swinging PVC strip curtains



Ceiling fixing (option)

■ 2620

FIXED STRIP CURTAIN / COMPOSITE

Quick and easy installation

Supplied with standard length mounting header (8 lengths)

For strips 190 x 2 mm with 40 and 80% overlap

For strips 300 x 3 mm with 50% overlap

Profile equipped with pre-assembled hooks ready for installation and suitable for both 40,50 and 80 % overlap

Profile and hooks manufactured in composite

■ 2600

FIXED STRIP CURTAIN / ANODISED ALUMINIUM

Supplied with standard length mounting header (22 lengths)

For strips 190 x 2 mm with 40 and 80 % overlapping

For strips 300 x 3 mm with 50 and 75 % overlapping

Profile and elements of profile manufactured in anodised Aluminium

■ 2700

SWINGING STRIP CURTAIN / ANODISED ALUMINIUM

Swinging in both directions for ease of access and increase the durability of the strips

Ceiling and/or panel mounting

Supplied with standard length mounting header (8 lengths)

Strips 190 x 2 mm or 300 x 3 mm

Overlap according to strip width

Profile and elements of profile manufactured in anodised Aluminium

DO IT YOURSELF STRIP CURTAIN

Header supplied in set lengths + accessories

Profile manufactured in either composite or anodised Aluminium dependent on which model selected

Strips 190 x 2 mm or 300 x 3 mm





Fixed and swinging PVC strip curtains

Features and advantages :

FERMOFLEX PVC strip curtains are suitable for a wide range of applications including cold rooms, hygiene areas and noise or light sensitive environments.

The profiles are very resistant to corrosion and easy to clean.

The strips can be fixed or replaced singularly.

Complying with the HACCP program, the FERMOFLEX strip curtains allow to:

- Minimise the temperature variations
- Increase the lifetime of the refrigeration components
- Save energy
- Avoid ice formation in negative temperatures and therefore improve Health & Safety

The strips material comply with the European food hygiene regulations.

STRIPS FEATURE


- Standard quality for positive temperature – 10°C to + 50°C
- Specific quality for negative temperature – 40°C to + 10°C
- Orange end strips only available in standard quality

On request:

- 190 mm x 4 mm PVC strips
- 300 mm x 4 mm PVC strips

OPTION

- Ceiling fixing (for ref. 2600 and 2620)



DISTRIBUTOR



FERMOD



3 avenue Eugène Gazeau - 60300 SENLIS - FRANCE
Tél. : +33 (0)3 44 53 12 86 - Fax : +33 (0)3 44 53 62 03
www.fermod.com • e-mail: contact@fermod.com

Siège Social : Senlis (Oise) - Société Anonyme au Capital de 1 004 400 €
RCS Compiègne B 301 468 211 - Siret 301 468 211 00018 - APE 2572 Z

12/07/2021

Imp. Polyservice - Beauvais

